

led profile

Our PROFESSIONAL led profile series for surfaces/hanging applications is manufactured in high purity aluminium and silver anodised. Its inner tray (where we can find the led and the power supply) can be removed from the front which means easy maintenance. It is suitable for hanging, surfaces and walls (providing Up&Down lighting); drivers can be housed inside. This profile can be combined with a white frosted cover ("easy-ON" system), to achieve a waterproofing of IP65 (very necessary in damp zones). We also have available Black&White covers and also microprism versions in transparent or frosted, which improve glare and UGR levels. Both profile and covers are available in lengths of 6m, allowing us to carry out long installations without joints.

We offer a 10 year guarantee on the profiles and 4 year guarantee on the covers.

MUNICH MAGNUM SLIM



IP65



Aluminium profile

17.004	anodised silver	6m
17.005	lacquered white	6m
17.006	lacquered black	6m



Aluminium tray

15.007	lacquered white	6m
--------	-----------------	----



"easy-ON" polycarbonate cover (Down)

18.070	frosted	6m
18.071	transparent microprism	6m
18.072	frosted microprism	6m
18.073	Black&White	6m



Aluminium endcaps with hole

19.234	anodised silver	
19.235	lacquered textured white	
19.236	lacquered textured black	



Methacrylate cover (UP)

18.014	transparent	2m
18.015	frosted	2m
18.016	transparent	6m
18.017	frosted	6m



Hanging kit

21.001	chrome	set of 2 units
21.002	white	set of 2 units
21.003	black	set of 2 units



Safety cable

22.039	steel 18cm	
--------	------------	--

Polycarbonate cover (UP)


18.146	frosted	2m
18.148	opal	2m
18.152	transparent	2m
18.145	frosted	6m
18.147	opal	6m
18.151	transparent	6m



Europäisches
Patentamt
European
Patent Office
Office européen
des brevets

Patente Europea
Nº.: 13156605.1

Aluminium alloy extrusion process in accordance with: ISO 9001:2008 - ISO 14001 / Tolerances: UNE-EN 755-9 / UNE-EN 12020-2 / Theoretical weight: 1.464Kg / Alloy: 6063 / Perimeter: 483mm / Anodising minimum: 15 microns Purity aluminium: 95-98% / Treatment: T-5 / Covers: Fireproof V0





90° angle bracket
22.049 aluminium

set of 2 units



Flat bracket
22.059 aluminium

set of 2 units



Joining plate
22.050 aluminium

set of 2 units