led profile

Our PROFESSIONAL led profile series for surface/hanging applications is manufactured in high purity aluminium, with 8 different colours to choose from.

The profile has an elegant hexagonal shape which can be rotated to achieve the desired lighting effect. Its inner tray (where we can find the led and power supply) can be removed from the front which means easy maintenance.

This profile can be combined with microprism covers both in transparent and frosted ("easy-ON" system), which improve glare and UGR levels. Both profile and covers are available in lengths of 6m, allowing us to carry out long installations without joints.

We offer a 10 year guarantee on the profiles and 4 year guarantee on the covers.




| Aluminium profile | | | | |
|-------------------|------------------------------------|----|--|--|
| 17.036 | azure blue lacquered (ral 5009) | 6m | | |
| 17.037 | white lacquered (ral 9003) | 6m | | |
| 17.038 | black lacquered (ral 9005) | 6m | | |
| 17.039 | patina green lacquered (ral 6000)) | 6m | | |
| 17.040 | stone grey lacquered (ral 7030) | 6m | | |
| 17.041 | pastel yellow lacquered (ral 1034) | 6m | | |
| 17.042 | tomato red lacquered (ral 3013) | 6m | | |
| 17.043 | ivory lacquered (ral 1014) | 6m | | |
| | | | | |



Aluminium endcaps

| 19.404 | azure blue lacquered (ral 5009) |
|--------|------------------------------------|
| 19.405 | white lacquered (ral 9003) |
| 19.406 | black lacquered (ral 9005) |
| 19.407 | patina green lacquered (ral 6000)) |
| 19.408 | stone grey lacquered (ral 7030) |
| 19.409 | pastel yellow lacquered (ral 1034) |
| 19.410 | tomato red lacquered (ral 3013) |
| 19.411 | ivory lacquered (ral 1014) |
| | |



Scale 1:1.3



"easy-ON" polycarbonate cover

| 18.070 | frosted | 6m |
|--------|------------------------|----|
| 18.071 | transparent microprism | 6m |
| 18.072 | frosted microprism | 6m |
| 18.073 | Black&White | 6m |



Aluminium tray


15.007 lacquered white



Hanging kit

| 21.001 | chrome | set of 2 units |
|--------|--------|----------------|
| 21.002 | white | set of 2 units |
| 21.003 | black | set of 2 units |





Ral colours











6m











A luminium alloy extrusion process in accordance with: ISO 9001:2015 / Tolerances: UNE-EN 755-9 / Theoretical weight: 2.101 kg / Alloy: 6063 / Perimeter: 885 mm / Anodisation minimum: 10 micras / Purity aluminium: 98.5% / Treatment: T-5

