led profile

Our PROFESSIONAL led profile series for hanging applications is manufactured in high purity aluminum, lacquered and textured in white or black. The power supply is external.

This profile uses 14 module reflectors and 2 different types of optics of 30° or 65°, improving visual comfort and guaranteeing a low UGR. It is suitable for rigid strips with a maximum width of 20mm, designed for the 14 module optical system. In addition, it has blind covers in white or black aluminum which can be placed in the final lengths of the luminaire and in the middle lengths where lighting is not required. The profile is available in lengths of 3.6 metres.

We offer a 5 year warranty on profiles.





Aluminium profile

13.036 lacquered white 3.6m 13.037 lacquered black 3.6m



Metal endcap

19.481 lacquered white 19.482 lacquered black



Reflector with 14 modules

46.072 white 280mm 46.073 black 280mm



Blind section

19.496 lacquered white 1m 19.497 lacquered black 1m




Blind section

19.475 lacquered white 19.476 lacquered black



Optics de with 14 modules

46.074 30° 280mm 46.075 65° 280mm



Scale 1:1 (Dimensions in mm)



Hanging KIT

set of 2 units 21.001 chrome 21.002 white set of 2 units 21.003 black set of 2 units



Rigid strip

36.068 3000K 280mm 36.069 4000K 280mm





Aluminium alloy extrusion process in accordance with: ISO 9001:2008 - ISO 14001 / Tolerances defined by: UNE-EN 755-9 / UNE-EN 12020-2 Theoretical weight: 0.664kg / Alloy: 6063 / Perimeter: 306mm / Anodising minimum: 15 microns / Aluminium purity: 95-98% / Material treatment: T-5